

Schalt- abstand	10,0 mm	12,0 mm	20,0 mm	22,0 mm	40,0 mm

Bauform	M12x1 3-Draht	M18x1 3-Draht	M18x1 3-Draht	M30 3-Draht	M30 3-Draht

Preis	35,50 €	35,50 €	35,50 €	45,50 €	45,50 €
Betriebs- spannung	10...30 V DC	10...30 V DC	10...30 V DC	10...30 V DC	10...30 V DC
Eigenstrom- aufnahme	< 10 mA	< 10 mA	< 10 mA	< 10 mA	< 10 mA
Ausgangs- strom	200 mA	200 mA	200 mA	200 mA	200 mA
Spannungs- abfall	< 2 V	< 2 V	< 2 V	< 2 V	< 2 V
Einschalt- verzögerung	< 50 ms	< 50 ms	< 50 ms	< 50 ms	< 50 ms
Schalt- hysterese	< 15 %	< 15 %	< 15 %	< 15 %	< 15 %
Schalt- frequenz	500 Hz	300 Hz	100 Hz	300 Hz	100 Hz
Umgebungs- temperatur	-25 ... +70°C	-25 ... +70°C	-25 ... +70°C	-25 ... +70°C	-25 ... +70°C
Schutz- art	IP 67	IP 67	IP 67	IP 67	IP 67
Gehäuse	Messing vernickelt	Messing vernickelt	Messing vernickelt	Messing vernickelt	Messing vernickelt
Bestellschlüssel					
PNP, Schließer	IS 64 DD	IS 44 DD	IS 70 DD	IS 50 DD	IS 76 DD
PNP, Öffner	IS 65 DD	IS 45 DD	IS 71 DD	IS 51 DD	IS 77 DD
NPN, Schließer	IS 61 DD	IS 41 DD	IS 67 DD	IS 47 DD	IS 73 DD
NPN, Öffner	IS 62 DD	IS 42 DD	IS 68 DD	IS 48 DD	IS 74 DD
Stecker	K	K	K	K	K